

Analogue CCTV / HD 4n1 / XVRs / Hikvision

DS-7204HGHI-M1(C)

HIKVISION



Features

- Hikvision
- DVR 5n1
- 4 HDTV/HDCVI/AHD/CVBS video CH
- 1 IP CH (up to 5 IP CH in total by substitution of analog channels)
- H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
- Maximum input resolution 1080p Lite
- Audio over coaxial
- Motion detection 2.0 on all analog channels
- Full HD HDMI and VGA Output
- Audio input and output

Specifications

Brand	HIKVISION
Range	VALUE
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	1 Additional CH IPs: Up to 5 IP channels (5 Mpx), replacing all BNC channels
Video outputs	1 HDMI Full HD and 1 VGA, simultaneous;
Display resolution	HDMI: 1920x1080, 1280x1024, 1280x720 / 60 Hz VGA: 1920x1080, 1280x1024, 1280x720 / 60 Hz
Audio inputs	Coaxial audio on all channels 1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input
Audio Bit Rate	64 Kbps
Audio compression	G.711u
Video compression	Analog channels: H.265 Pro+ / H.265 Pro / H.265 / H.264+ / H.264 IP channels: H.265+ / H.265 / H.264+ / H.264
Recording resolution	1080p Lite/ 720p Lite/ VGA/ WD1/ 4CIF/ CIF
Input resolution	HDTVI: 1080p (25~30 fps), 720p (25~30 [%VAR%] fps) HDCVI: 1080p (25~30 fps), 720p (25~30 [%VAR%] fps) AHD: 1080p (25~30 fps), 720p (25~30 [%VAR%] fps) CVBS: PAL/NTSC
Main Stream coding	For the 1080p stream: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF (25 fps) For the 720p stream: 720p/WD1/4CIF/VGA/CIF (25 fps) For SD stream: WD1/4CIF/VGA/CIF (25 fps (P), 30 fps (N))
Extra Stream coding	4CIF (15 fps); CIF/QVGA (25 fps (P), 30 fps (N))
Video Bit Rate	32 Kbps at 4 Mbps
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	Does not have
Motion Detection	Motion detection 2.0 with human and vehicle classification applied in motion detection. Available on all analog channels.
Recording method	Manual, programmed, motion detection

Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	1 SATA HDD 3.5" of up to 4 TB (not included)
Communication	2 x USB 2.0 (rear side) / 1 x RJ45 (Ethernet)
Remote connections	32
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Power	DC 12 V, 1.5 A, ? 16 W (no HDD)
Operating temperature	-10° ~ +55° C
Dimensions / Weight	45 (H) mm x 260 (W) mm x 222 (D) mm / ? 0.8 Kg (w/o HDD)